

The glass microbeads in the road mixture are used as the reflexive component in paint for the realisation of road markings. The graded fractions are used for jet spraying surfaces.

TECHNICAL PARAMETERS: specific weight 2.45 kg/dm³
 refractive index 1.50
 hydrolytic class IV

GRANULOMETRY:

THE ROAD MIXTURE

COMMERCIAL NAME (MICROMETERS) (%)

BMX 40	500 - 630	0 - 10
	400 - 500	10 - 30
	315 - 400	30 - 70
	200 - 315	10 - 50
	100 - 200	0 - 10
	50 - 100	0 - 5

COMMERCIAL NAME (MICROMETERS) (%)

BMX 60	400 - 500	0 - 10
	315 - 400	5 - 30
	200 - 315	30 - 70
	100 - 200	10 - 40
	50 - 100	0 - 10
	under 50	0 - 5

GRADED FRACTIONS

COMMERCIAL NAME (MICROMETERS)

B 7	570 - 700
B 8	430 - 570
B 9	325 - 430
B 10	200 - 300
B 112	150 - 250
B 134	100 - 200
B 159	70 - 110

PACKAGING: bags with a net weight of 25 kg, 40 bags on 1 pallet = 1t (a pallet – 1000 kg net)

We always require cash payments up to an invoice value of 10,000 CZK!
It is possible to arrange a discount upon the accumulation of your annual orders.

DELIVERY TERMS: personal collection, direct credit, pick-up service